

# Technical specs

## VE509 - TOUTRAVO 509 (921U-75.30)

**Name:**

BLACK NEOPRENE GLOVE LENGTH 30 CM

**Size:**

6/6,5 - 7/7,5 - 8/8,5 - 9/9,5 - 10/10,5

**Colour:**

Black



**Description :**

Extra heavy weight Neoprene glove, cotton flock lining, grip-pattern palm and fingers, straight cuff. Length: 30 cm, thickness: 0.75 mm. Bacteriostatic and fungistatic additive.

**Materials:**

100% neoprene  
100% cotton flock lining

**Strong points:**

Waterproof gloves- Textured palm and fingers. Excellent chemical resistance. Very good abrasion resistance.

**Instructions for use:**

All-purpose protective glove against mechanical, chemical and microorganic risks.

**Limits to use:**

Do not use this glove out of its usage specifications defined in the instructions above. Do not use it with irritant, toxic or corrosive chemicals other than those above mentioned without previous tests. This glove does not contain substance known as being carcinogenic, neither toxic, nor likely to cause allergies to the sensitive people.

**Instructions for storage:**

Keep in its original packing away from light and humidity.

**Instructions for cleaning / maintenance:**

Rinse under cold or tepid water, and leave to dry. No other specific maintenance for this type of glove.

**Performances :**

This glove complies with the European directive 89/686, notably regarding ergonomics, innocuousness, comfort, ventilation and flexibility, with EN420:2003 (dextérité 5), EN388:2003 (4,1,1,0) and EN374-3:2003 (ABCIJ) levels of permeation from 1 to 6 (A : Methanol = 3, B : Acetone = 3, C: Acetonitrile = 1, I: Ethyl Acetate = 3, J : n-Heptane = 2, Chrystallisabel acetic acid = 6, acetic acid 25% = 6, Aniline = 6, Dimethylformamide = 6, Ethanol = 6, Formaldehyde 37% = 6, Furfural = 6, Hydrochloric acid 10% = 6, Nitromethane = 6, Octyl alcohol = 6, Phenol = 6, Sodium hydroxide (20%) = 6)

- **EN388:2003** Protective gloves against mechanical Risks (Levels obtained on the palm)



4 : Resistance to abrasion (from 0 to 4)  
1 : Resistance to cut (from 0 to 5)  
1 : Resistance to tear (from 0 to 4)  
0 : Resistance to perforation (from 0 to 4)

# Technical specs

## VE509 - TOUTRAVO 509 (921U-75.30)

- **EN420:2003** General requirements
  
- **EN374-3:2003** Protective gloves against chemicals and micro-organisms - Part 3: Determination of resistance to permeation by chemicals



ABCIIJ : Resistant gloves to permeation by chemicals, tested according to EN374-3