


Deckplate Connect Interlocking tile version of our popular dual-layer mat

- ٠
- Interlocking tile version of our popular dual-layer mat Interlocking tile modules designed to cover unusual or large floor . areas.
- Simply connect mats together in any configuration to create a . seamless ant-fatigue surface.
- Self-extinguishing top surface provides resilience to many . industrial chemicals.
- Comfortable foam 'cushion' backing for fatigue relief. Ramped edges reduce the risk of trips. •
- •







Technical Specification

Material:	PVC	
Backing:	PVC foam (fusion bonded, not glued)	
Surface Finish:	Diamond pattern	
Product Height:	14mm	
Operating Temperature:	0°C to +60°C	
Resistant to Chemicals:	The upper surface of the PVC provides limited resistance to chemicals and oils	
Environmental Resistance:	Suitable for dry indoor environments	
Typical Applications:	Packing stations, assembly areas, production lines where regular turning occurs	
Installation Method:	Loose lay	
Cleaning Method:	Brush/Mop the top surface	
Country of Origin:	China	
Notes:	Please ensure Deckplate Connect is laid on a smooth floor surface to ensure integrity of connections'	

Sizes	Black	Weight
50cm x 50cm (Middle)	DP010008	2.00 kg
50cm x 50cm (End)	DP010009	2.00 kg
50cm x 50cm (Corner)	DP010010	2.00 kg