# FORCES PRESSUCHECK FORCES & PRESSUCHECK WITH DAILY FACE FIT CHECK TECHNOLOGY

Face-fit testing is reassuring but how can you be sure that you have donned the mask correctly each time you wear it? With PressToCheck™ filters you can instantly check that you have the correct seal every time you don your mask before entering the hazard zone.



#### 🗾 SUPERIOR COMFORT & FIT

Thermoplastic rubber mask available in three sizes for superior fit to most face shapes. Adjustable 4-point cradle ensures an effective facial fit.



**TYPHOON™ VALVE** Low resistance exhalation valve for easy breathing, with stable mask configuration. Made from silicone it performs well at very



# **COMPATIBILITY**The low-profile, swept-back design Force<sup>™</sup>8

The low-profile, swept-back design Force<sup>™</sup>8 PressToCheck<sup>™</sup> enables excellent visibility, allowing the filters to be worn effectively behind all types of faceshield and welding visor.

### 🗸 FIT IT



**DON THE MASK** Put the straps and harness over your head and pull the straps to a suitably tight and comfortable fit.

### V PRESS IT



low temperatures.

**PRESS**TO**CHECK**<sup>™</sup> Press the front and backs of both filter covers together to stop air from entering through the filters.

## CHECK IT



INHALE - No air should come through the mask.
Iook forward and adjust the mask until a seal is created. Repeat this process whilst looking 2 up,
down, 4 left and 5 right to complete the check.

















www.jspsafety.com sales@jspsafety.com UK tel: +44 (0)1993 826050